





# Low Intermodulation Termination

## Features and Electrical specifications:

Model	CT-200W-FX1720-IP65-NK/0.35-6G
Frequency Range	0.35~6.0GHz
VSWR	1.30 Max@0.35~6.0GHz
PIM3	≤-150dBc/-155dBc/-160dBc @2*43dBm
Power	200W
Impedance	50 Ω
Connector Type	N-F (K)
Waterproof Grade	IP65 or IP67
Dimension	200x170x64mm
Operating Temperature	-35 ~ +75°C (See de Power De-rating)
Color	Black

## Outline Drawing (Unit: mm/inch):



**RFTYT Technology Co., LTD.**

<http://www.rftyt.com>

E-mail: [jackson@rftyt.com](mailto:jackson@rftyt.com)      [zqc7708@rftyt.com](mailto:zqc7708@rftyt.com)

TEL: +86-13088268828      FAX: +86-816-2846565

218# Wenwu Middle Road, Jinkai District, Mianyang, Sichuan Province China


**Ready For Tackling Your Trouble**



Use attention:

- 1、Dimensions Tolerance  $\pm 5\%$ ;
- 2、If necessary, the product shall be air-cooled for auxiliary heat dissipation;
- 3、Custom designs available of other special Coaxial Terminations;
- 4、Pay attention to the direction of the product during use and strictly prohibit reverse connection.

Power De-rating:



P/N Designation:

